



# FilSafe

## Tank Monitoring System Float Operated Alarm LD Series 101

### APPLICATION

The FilSafe Tank Monitoring Alarm Unit LD Series 101, provides an **Over-Fill** level alarm for 1 tank, and is mostly used in Diesel Oil or Water tanks.

The unit comes complete with a 1 metre adjustable level float switch that makes this a highly reliable **Over-Fill** alarm system.

- **Helps to avoid Liquid Spillage**
- **Continuously monitors tank**
- **Mains Powered**
- **Built in Sounder**



### Alarm Unit Specification

Supply:	230V 50Hz
Max. current draw:	250mA
Enclosure:	Weatherproof IP54 grey ABS.
Dimensions:	158 x 115 x 76 mm deep
Temperature Range:	-10/+50°C
Electrical entry:	1 x 16mm & 1 x 20mm glands
Weight:	0.5kg

### Float switch

Construction	
Connecting head:	Cast aluminium
Connection:	1"bsp brass male
Tube:	Brass (Customer cut to length)
Float assembly:	Polypropylene

Full fitting instructions supplied with each unit.



**T. J. Williams Ltd** [www.tjwilliams.co.uk](http://www.tjwilliams.co.uk)

Wimborne Road,  
Barry,  
Vale of Glamorgan  
CF63 3DH

Tel 01446 729200  
Fax 01446 739281

Data Sheet **FSU LD101** 21/10/2016